

Manufacturer	Model	(1) Avg. Weight Emissions (g/hr)	(2) Avg. B415.1 Efficiency	(3) Emission Rate: Category 1 (g/hr)	Emission Rate: Category 2 (g/hr)	Emission Rate: Category 3 (g/hr)	Emission Rate: Category 4 (g/hr)	(4) Test Method: Method 28 or ASTM E2779-10 & 5G or 5H	(5) Lab	(6) Test Date	(7) Pellet Fuel Name/ Moisture/ Ash Content
England Stove Works, Inc.	PDVC55	3.1	N/A*	5.65	2.19	2.36, 2.62	N/A*	Method 28 & 5G-3	Intertek	02/13-15/2001	Moisture: Dry: 7.38% Wet: 6.88% Ash: N/A*
Gruppo Piazzetta S.P.A.	Sabrina	2.3	N/A*	1.57	2.19	2.77	3.20	Method 28 & 5G	Intertek	08/6-7/2012	Moisture: Dry: 3.6% Wet: 3.5% Ash: N/A*
Hearth & Home Technologies	Mt. Vernon E2	2.7	N/A*	N/A*	1.70, 1.81	3.13	5.88	Method 28 & 5G	OMNI	09/17-18/2013	Moisture: Dry: 4.51% Wet: N/A* Ash: N/A*
Hearth & Home Technologies	Mt. Vernon E2	0.5	<del>CBI**</del> <b>75</b>	N/A*	0.39, 0.44	0.58	0.98	Method 28 & 5G	Intertek	10/21-22/2014	Moisture: Dry: 2.39% Wet: 2.33% Ash: N/A*
Hearth & Home Technologies	Mt. Vernon AE	1.7	<del>CBI**</del> <b>71</b>	1.06	0.89	1.13	1.97	Method 28 & 5G2	Intertek	08/5-6/2014	Moisture: Dry: 5.44% Wet: 5.16% Ash: N/A*
Hearth & Home Technologies	Accentra 52i insert	1.5	<del>CBI**</del> <b>76</b>	1.02	0.80	1.21	5.61	Method 28 & 5G	OMNI	11/11-13/2014	Moisture: Dry: 5.63% Wet: 5.33% Ash: 0.50%

Manufacturer	Model	Avg. Weight Emissions (g/hr)	Avg. B415.1 Efficiency	Emission Rate: Category 1 (g/hr)	Emission Rate: Category 2 (g/hr)	Emission Rate: Category 3 (g/hr)	Emission Rate: Category 4 (g/hr)	Test Method: Method 28 or ASTM E2779-10 & 5G or 5H	Lab	Test Date	Pellet Fuel Name/ Moisture/ Ash Content
Hearth & Home Technologies	Absolute 43	1.8	N/A*	1.41	1.42	2.22	2.54	Method 28 & 5G	OMNI	08/12-14/2014	Moisture: Dry: 5.98% Wet: N/A* Ash: N/A*
Ravelli	RV 80	3.0	<del>CBI**</del> <b>56</b>	N/A*	3.00, 3.53	2.40, 2.81	N/A*	Method 28 & 5G-3	PolyTests	05/6-8/2013	Moisture: Dry: 6.53% Wet: 6.13% Ash: N/A*
Ravelli	RV 100	2.9	<del>CBI**</del> <b>70</b>	3.41	2.80	2.58, 3.13	N/A*	Method 28 & 5G-3	PolyTests	05/9, 13, 14/ 2013	Moisture: Dry: 6.53% Wet: 6.13% Ash: N/A*

Manufacturer	Model	Avg. Weight Emissions (g/hr)	Avg. B415.1 Efficiency	Emission Rate: Category 1 (g/hr)	Emission Rate: Category 2 (g/hr)	Emission Rate: Category 3 (g/hr)	Emission Rate: Category 4 (g/hr)	Test Method: Method 28 or ASTM E2779-10 & 5G or 5H	Lab	Test Date	Pellet Fuel Name/ Moisture/ Ash Content
Sherwood Industries, Ltd.	M55	1.0	N/A*	1.12	1.14	0.92	0.91	Method 28 & 5H	OMNI	10/15, 18/2010	Moisture: Dry: Run 1: 2.97% Run 2: 2.98% Run 3: 2.975% Run 4: 2.98% Wet: Run 1: 2.88% Run 2: 2.89% Run 3: 2.89% Run 4: N/A* Ash: N/A*

Manufacturer	Model	Avg. Weight Emissions (g/hr)	Avg. B415.1 Efficiency	Emission Rate: Category 1 (g/hr)	Emission Rate: Category 2 (g/hr)	Emission Rate: Category 3 (g/hr)	Emission Rate: Category 4 (g/hr)	Test Method: Method 28 or ASTM E2779-10 & 5G or 5H	Lab	Test Date	Pellet Fuel Name/ Moisture/ Ash Content
Travis Industries, Inc.	AGP Insert	0.67	N/A*	0.55	0.36	0.52	2.37	Method 28 & 5G-2	Intertek	05/5-6/2014	Moisture: 6.5% Wet: 6.1% Ash: N/A*

### Legend

1. Average weighted grams per hour Particulate Matter (PM) emissions.
2. Average B415.1 efficiency per wood heater.
3. Grams per hour PM emissions for individual burn categories for all the test runs that are reported on the summary sheet from the EPA accredited test labs. These stoves will have a minimum of 4 test runs at 4 burn rates.
4. Test method used: Method 28 or ASTM E2779-10 and 5G or 5H.
5. The name of the EPA accredited lab that performed the testing for each of the stoves.
6. Date of the testing at the EPA accredited lab.
7. Moisture and Ash Content of the pellet fuel used during testing.

\* N/A- Not provided by Lab.

\*\* CBI- Further inquiry to determine if listed as Confidential Business Information.