




Twin Ports Testing, Inc.  
 1301 North 3rd Street  
 Superior, WI 54880  
 p: 715-392-7114  
 p: 800-373-2562  
 f: 715-392-7163  
 www.twinportstesting.com

**Report No:** USR:W215-1331-01  
**Issue No:** 1

## Analytical Test Report

**Client:** ALLIANCE FOR GREEN HEAT  
 512 Elm Avenue  
 Takoma Park, MD 20912  
**Attention:** John Ackerly  
**PO No:**

Signed:   
 Stephen Sundeen  
 Chemistry Laboratory Manager  
 Date of Issue: 12/23/2015  
THIS DOCUMENT SHALL NOT BE REPRODUCED EXCEPT IN FULL

Sample Details			
<b>Sample Log No:</b>	W215-1331-01	<b>Sample Date:</b>	
<b>Sample Designation:</b>	Pellet Sample	<b>Sample Time:</b>	
<b>Sample Recognized As:</b>	Pellets	<b>Arrival Date:</b>	12/17/2015

Test Results				
	METHOD	UNITS	MOISTURE FREE	AS RECEIVED
Moisture Total	ASTM E871	wt. %		5.71
Ash	ASTM D1102	wt. %	0.49	0.46
Volatile Matter	ASTM D3175	wt. %		
Fixed Carbon by Difference	ASTM D3172	wt. %		
Sulfur	ASTM D4239	wt. %	0.012	0.011
SO <sub>2</sub>	Calculated	lb/mmbtu		0.027
Net Cal. Value at Const. Pressure	ISO 1928	GJ/tonne		
Net Cal. Value at Const. Pressure	ISO 1928	J/g		
Gross Cal. Value at Const. Vol.	ASTM E711	J/g	19760	18632
Gross Cal. Value at Const. Vol.	ASTM E711	Btu/lb	8496	8011
Carbon	ASTM D5373	wt. %		
Hydrogen*	ASTM D5373	wt. %		
Nitrogen	ASTM D5373	wt. %		
Oxygen*	ASTM D3176	wt. %		
*Note: As received values do not include hydrogen and oxygen in the total moisture.				
Chlorine	ASTM D6721	mg/kg		
Fluorine	ASTM D3761	mg/kg		
Mercury	ASTM D6722	mg/kg		
Bulk Density	ASTM E873	lbs/ft <sup>3</sup>		
Fines (Less than 1/8")	TPT CH-P-06	wt. %		
Durability Index	Kansas State	PDI		
Sample Above 1.50"	TPT CH-P-06	wt. %		
Maximum Length (Single Pellet)	TPT CH-P-06	inch		
Diameter, Range	TPT CH-P-05	inch		to
Diameter, Average	TPT CH-P-05	inch		
Stated Bag Weight	TPT CH-P-01	lbs		
Actual Bag Weight	TPT CH-P-01	lbs		

**Comments**